

Demolition Quick-Clamp

SUI's Demolition Quick-Clamp, is an innovative design of the Coupler Bucket with its light, yet durable Non-Link Thumb. Effectively maintains the time saving advantages gained by the application of a quick Coupler, while providing your excavator with imporved versatility and maximized performance.

	Model	Weight	Max. Operating Pressure	Max. Throat Opening
1	SUISL24DQC	980 lbs.	1,800 psi	45"
	SUISL30DQC	1,000 lbs.	1,800 psi	45"
	SUI3036DQC	2,475 lbs.	3,000 psi	71"
	SUI3042DQC	2,585 lbs.	3,000 psi	71"
	SUI4042DQC	3,630 lbs.	3,500 psi	84"
	SUI4048DQC	3,960 lbs.	3,500 psi	84"
	SUI5548DQC	5,390 lbs.	3,500 psi	86"
	SUI5554DQC	5,830 lbs.	3,500 psi	86"
	SUI7054DQC	6,490 lbs.	3,500 psi	91"
	SUI7060DQC	6,930 lbs.	3,500 psi	91"
	SUI10060DQC	8,360 lbs.	3,500 psi	116"
	SUI10072DQC	8,800 lbs.	3,500 psi	116"
	SUI15060DQC	13,310 lbs.	3,500 psi	118"
	SUI15072DQC	14,234 lbs.	3,500 psi	118"
	SUI15078DQC	15,290 lbs.	3,500 psi	118"

Due to SUi's policy of ongoing improvements, specifications could change without notice.

